15" (13.8" VIS) Color Monitor With Outstanding Performance At An Incredible Price

- Crisp, clear display that's easy on the eyes. This monitor, with high contrast tube, has a fine dot pitch and non-glare tube which ensures crisp, clear graphics and text that are easy on the eyes, even after hours of continuous use
- **Superior performance.** With a maximum resolution of 1024 x 768 at 75Hz, the 105S provides superior performance required by today's demanding applications
- Screen adjustments made easy. Convenient digital controls allow you to make quick and easy screen adjustments, and 6 user memories eliminate aggravating screen adjustments when switching resolutions
- A monitor you can rely on.

A 60,000-hour-mean-time-between-failure (MTBF) rating makes it one of the most reliable monitors on the market, backed by the world's second largest monitor maker, with an exceptional warranty of 3 years parts and labor for your investment

• Incredible value for a 15" monitor. The outstanding performance and features of the 105S result in a monitor which is as easy on your eyes as it is on your wallet



PRODUCT NUMBER 15C3220W TECHNICAL SPECIFICATIONS:

REGULATORY APPROVALS

CSA FCC-B CE MPR-II **SEMKO** TUV/GS TUV-ERGO **DHHS**

LOW-EMISSION CHARACTERISTICS

Complies with MPR-II Specifications CONTROLS AND CONNECTIONS

Front: - Power On/Off

- 4 Control Buttons

Rear:

- Power Input Socket - 15-Pin D-Sub Input Socket

Cables:

- Detachable Power Cord - Fixed D-Sub Interface Cable - Switchless Mac® Adaptor

Digital Controls:

- Brightness - Contrast
- H-Size
- V-Size
- H-Position
- V-Position
- Reset
- Pincushion
- Trapezoid
- Color Temperature
- Parallogram
- Monitor Status

PHYSICAL SPECIFICATIONS

Standard Series Monitor

Unit Dimensions 14.3"W x 14.6"H x 15.6"D/ 363 x 371 x 396 mm (including pedestal) Unit Weight 27.5 lbs./12.5 kg. Carton Dimensions 19.2"W x 16.3"H x 17.4"D/ 488 x 414 x 443 mm 30.8 lbs./14.0 kg. Carton Weight **UPC** Code 0 37849 86854 6 **Power Supply** 90 - 264 Vac, 50/60Hz Power Consumption 90 Watts Maximum 32°F to 104°F/ Operating Temperature 0°C to 40°C 10% to 90% Relative Humidity Storage Temperature -13°F to 149°F/ -25°C to 65°C Relative Humidity 5% to 95% >60,000 Hours **MTBF**

WARRANTY

3 year parts and labor

(excluding CRT)

Carton contains: 105S Color Monitor, Tilt and Swivel Base, VGA Cable, Switchless Mac Adaptor, Power Cable, Users Manual, and Warranty Card.

The EPA ENERGY STAR emblem does not represent EPA endorsement of any product or service. As an ENERGY STAR Partner, Philips has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

Mac is a registered trademark of Apple Computer, Inc.

VESA is a registered trademark of the Video Electronics Standards Association.

VGA and SVGA are registered trademarks of International Business

Machines Corp.
Windows is a registered trademark of Microsoft Corp.
Specifications subject to change without notice.

Printed in the LLS A ©1998 Philips Consumer Electronics Co.
A Division of Philips Electronics North America Corp. KX98.0146 KID Design, Philips Consumer Electronics Co

FOR MORE INFORMATION

Internet Address: http://www.philipsmonitors.com FAX INFORMATION SYSTEM: (423) 521-4341 TECHNICAL SUPPORT: (800) 835-3506 (USA) (423) 475-0280 (outside USA)

Literature order form: 15C3220WA

CRT

Size and Deflection 15"/38 cm, 90° VIS 13.8" Horizontal Pitch 0.24 mm Dot Pitch 0.28 mm Flat Square Tube Type Invar Shadow Mask Screen Coating **AGAS** 57% Light Transmission Phosphor Recommended Display Area 10.6" x 8.0"/ 270 x 202 mm 11.2" x 8.4"/ Maximum Display Area 284 x 213 mm

SCANNING

30 - 60kHz Horizontal Frequency 50 - 120Hz Vertical Frequency

VIDEO

Video Dot Rate 79MHz Input Impedance: 75Ω - Video $2.2~k\Omega$ Input Signal Levels: .7Vp-p or 1.0Vp-p Separate Sync - Sync Input Signal Composite Sync

DISPLAY AND PERFORMANCE PARAMETERS

White Color Temperature and Chromaticity CIE Coordinates:

at 9300°K: y = 0.311at 6500°K: x = 0.313y = 0.329

RESOLUTION AND PRESET MODES

Maximum Resolution 1024 x 768 @ 75Hz 9 User Definable Modes

9 Factory Preset Modes:

H. Freq.	V. Freq. Standard	
(kHz)	(Hz)	
31.5	70	VGA®
31.5	60	VGA
37.5	75	VESA®/75
43.3	85	VESA®/85
37.8	60	SVGA®
46.9	75	VESA®/75
53.7	85	VESA®/85
48.4	60	XGA
60.0	75	VESA®/75
	(kHz) 31.5 31.5 37.5 43.3 37.8 46.9 53.7 48.4	(kHz) (Hz) 31.5 70 31.5 60 37.5 75 43.3 85 37.8 60 46.9 75 53.7 85 48.4 60

PLUG-AND-PLAY COMPATIBILITY

Display Data Channel DDCI/2B (VESA)

POWER MANAGEMENT

Complies with EPA Energy Star and **NUTEK Specifications** Philips Magnavox 105S consumes less than 8 watts in Power Off mode



